
KombiSIGN 40 / ClassicLOOK

TwinLIGHT Classic 24VAC/DC RD



Part No.:	**634.110.75**
Series:	**KombiSIGN 40**

MECHANICAL DATA	
Height	59 mm
Diameter	40 mm
Materials	PC
Dome colour	Red
Protection category	IP66 IP69K
Service life optical	50,000 h maximum
Working temperature minimum	-30°C
Working temperature maximum	+60°C
UL Type Rating	Type 12
Weight with packaging	39 g
Product weight	29 g

ELECTRICAL DATA	
Operating voltage	24V
Operating voltage type	AC/DC
Operating voltage frequency	50Hz
Operating voltage tolerance	+/- 10%
Rated operational voltage	24 VDC
Rated operational current	30 mA
Rated inrush current	500 mA
Protection class	Protection class 3
Pollution degree	3
Request to external PSU	SELV/PELV


OPTICAL DATA	
Light source	LED
Light colour	Red
Optical signal image	TwinLight
Blink frequency (Hz)	1 Hz

! For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.

KombiSIGN 40 / ClassicLOOK

TwinLIGHT Classic 24VAC/DC RD

DRAWING



! For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.