Monitorable Beacons / Monitorable LED Signal Beacon 806

# Monit. LED Beacon BWM 24VDC YE




**Part No.: 806.350.55**

| MECHANICAL DATA | |
|---|---|
| Height | 108 mm |
| Diameter | 75 mm |
| Materials | PA-GF<br>PC<br>PC/ABS |
| Dome colour | Yellow |
| Housing colour | Black |
| Protection category | IP65 |
| Connection | Spring-type terminal |
| cross-sectional area maximum | 2,50mm² / 14AWG |
| Cable entry | Through hole |
| Cable entry maximum | d = 14 mm |
| Type of fixing | Base mounting<br>Wall mounting |
| Service life optical | 100,000 h maximum |
| Working temperature minimum | -20°C |
| Working temperature maximum | +50°C |
| UL Type Rating | Type 12 |
| Weight with packaging | 154 g |
| Product weight | 121 g |

| ELECTRICAL DATA | |
|---|---|
| Operating voltage | 24V |
| Operating voltage type | DC |
| Operating voltage tolerance | +/- 10% |
| Rated operational voltage | 24 VDC |
| Rated operational current | 60 mA |
| Rated inrush current | 60 mA |
| Protection class | Protection class 2 |
| Pollution degree | 3 |


| OPTICAL DATA | |
|---|---|
| Light source | LED |
| Light colour | Yellow |
| Optical signal image | Permanent |

! For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.

Monitorable Beacons / Monitorable LED Signal Beacon 806

# Monit. LED Beacon BWM 24VDC YE

**DRAWING**




! For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.