Baumer
Passion for Sensors

Load cells


DLM40-IN

Compact inline load cells for industrial applications

DLM40-IN.###.TP3.C4

Overview

- Tension and compression load till 20 kN
- Non-linearity < 0.2 %
- One-sided stop with integrated hexagon for easy mounting
- Sensor body made of stainless steel with protection class IP68
- Fully welded sensor design
- Durable with 100% working stroke



c UL us

Technical data

general data	
Measuring range	0 ... 20 kN
Non-linearity	< 0.2 %
Repeatability	< 0.1 %
Temperature effect zero	< 0.2 % / 10K
Zero point deviation	< 20 %
Type	Inline
Mechanical mounting	M12 thread / M12 thread
electrical data	
Nominal sensitivity	1 mV/V
Bridge resistance	1000 Ω
Supply voltage	0.5 ... 12 VDC
Signal polarity positive	Tension
mechanical data	
Overload	150 %
Breaking load	200 %

mechanical data	
Nominal displacement	40 µm
Weight	230 g
Material sensor body	Stainless steel, 1.4542
Fatigue strength	>10 Mio cycles at 0...100% FS
Electrical connection	M8, 4 pin, male
environmental conditions	
Operating temperature range	-40 ... 85 °C
Storage temperature range	-40 ... 85 °C
Protection class EN 60529, ISO20653	IP 68
compliance and approvals	
EMC	EN 61000-6-2 EN 61000-6-3 EN 61326-2-3
UL listed	E217824


2020-01-27 The product features and technical data specified do not express or imply any warranty. Technical modifications subject to change.

DLM40-IN


Compact inline load cells for industrial applications

DLM40-IN.###.TP3.C4

Dimensional drawings



Electrical connection



1 +Vs
2 Sig +
3 –Vs
4 Sig –

Ordering key - Configuration possibilities see website

	DLM	40	-	IN	.	###	.	T	P3	.	C4
Product group											
Membrane force sensor	DLM										
Size category											
40		40									
Type											
Inline				IN							
Max. nominal force											
2 kN						202					
5 kN						502					
10 kN						103					
20 kN						203					
Measuring direction positive											
Tension								T			
Ouput signal											
Nominal sensitivity 1.00 mV/V									P3		
Electrical connection											
M8, 4 pin, male											C4

2020-01-27 The product features and technical data specified do not express or imply any warranty. Technical modifications subject to change.