Incremental encoders


ITD21H01 HT

Through hollow shaft ø14 mm

100…8192 pulses per revolution

Overview

- Size ø58 mm
- Precise optical sensing
- Output signal level TTL
- Through hollow shaft, ø14 mm
- For cone clamping installation
- Max. 8192 pulses per revolution
- Operating temperature -30...+120 °C
- Detachable cable – tangential outlet



Technical data

Technical data - electrical ratings	
Voltage supply	5 VDC ±5 %
Reverse polarity protection	Yes
Consumption w/o load	≤100 mA
Pulses per revolution	100 … 8192
Reference signal	Zero pulse, width 90°
Sensing method	Optical
Output frequency	≤300 kHz (TTL)
Output signals	A, B, N + inverted
Output stages	TTL linedriver (short-circuit proof)
Interference immunity	DIN EN 61000-6-2
Emitted interference	DIN EN 61000-6-3
Technical data - mechanical design	
Size (flange)	ø58 mm

Technical data - mechanical design	
Shaft type	ø14 mm (through hollow shaft)
Protection DIN EN 60529	IP 54
Operating speed	≤6000 rpm
Starting torque	≤0,015 Nm (+20 °C)
Material	Housing: aluminium Shaft: stainless steel
Operating temperature	-30...+120 °C
Relative humidity	90 % non-condensing
Resistance	DIN EN 60068-2-6 Vibration 20 g, 60-2000 Hz DIN EN 60068-2-27 Shock 100 g, 6 ms
Connection	Board connector, 8-pin
Weight approx.	150 g


2020-02-11 The product features and technical data specified do not express or imply any warranty. Technical modifications subject to change.

ITD21H01 HT

Through hollow shaft ø14 mm
100…8192 pulses per revolution

Terminal assignment


Connector	Assignment
Pin 1	UB
Pin 2	GND
Pin 3	Track A
Pin 4	Track A inv.
Pin 5	Track B
Pin 6	Track B inv.
Pin 7	Track N
Pin 8	Track N inv.



Output signals

Clockwise rotation when looking at the mounting side.

NI-Output signals



Trigger level

Outputs	**Linedriver**
Output level High	≥2.4 V
Output level Low	≤0.5 V
Load	≤70 mA


2020-02-11 The product features and technical data specified do not express or imply any warranty. Technical modifications subject to change.

ITD21H01 HT

Through hollow shaft ø14 mm

100…8192 pulses per revolution

Dimensions



2020-02-11 The product features and technical data specified do not express or imply any warranty. Technical modifications subject to change.

ITD21H01 HT

Through hollow shaft ø14 mm
100…8192 pulses per revolution

Ordering reference

	ITD21H01	####	T	NI	S21SG8	F	14	54	019
Product									
	ITD21H01								
Pulse number									
100		100							
120		120							
128		150							
200		200							
250		250							
256		256							
300		300							
360		360							
400		400							
500		500							
512		512							
600		600							
720		720							
900		800							
900		900							
1000		1000							
1024		1024							
1200		1200							
1250		1250							
1250		1440							
1250		1500							
1800		1800							
2000		2000							
2048		2048							
2500		2500							
3000		3000							
3600		3600							
5000		4000							
4096		4096							
5000		5000							
6000		6000							
8192[1]		8192							
Voltage supply									
UB= 5 VDC ±5% / TTL level, linedriver			T						
Output signal									
A, A inv, B, B inv, N, N inv				NI					
Connection									
Board connector type 21, pin contacts, straight, 8-pin					S21SG8				
Operating temperature									
-30...+120 °C						F			
Through hollow shaft									
Ø14 mm, for cone clamping installation (equipment)							14		
Protection class									
IP54								54	
Mounting kit									
3-arm, pitch circle diameter 76 mm, mounting 3 × M3 (120°)									019

The product features and technical data specified do not express or imply any warranty. Technical modifications subject to change.
2020-02-11

Ordering reference

(1) Pulse numbers are interpolated.

Accessories

Mounting accessories

11073114	Torque arm, 3-armed, bolt circle ø76 mm, mounting M3 (mounting kit 019)
11073115	Cone spreader shaft ø10 mm
11073116	Cone spreader shaft ø10 mm V1
11073117	Cone spreader shaft ø14 mm

Connectors and cables

11071187	Connection cable with FCI, 8-pin / wire end sleeves, 0.6 m
11071188	Connection cable with FCI, 8-pin / wire end sleeves, 1 m
11112263	Connection cable with FCI, 8-pin / wire end sleeves, 3 m
11071189	Connection cable with crimp contacts, 0.2 m

2020-02-11 The product features and technical data specified do not express or imply any warranty. Technical modifications subject to change.